

| | | | | |
|---|-------------------------------|--|--------------------------------------|--|
| 246 | Subase Kings Bay, Georgia | | Waste Information Document (WID) | |
| As of 9/21/2020 | | | WID Number 1268 - 246 | |
| Waste Description: CORROSION PREVENTIVE LIQUID - FLAMMABLE | | | | |
| Waste Material label required?: YES | | | Hazardous Waste label required?: YES | |
| Waste Generation Process: THIS PRODUCT USED IN MACHINERY DURING SHIPMENT TO PREVENT CORROSION. PRODUCT HAS EXPIRED SHELF LIFE, IN DAMAGED OR OPENED CONTAINER(S). | | | | |
| Waste Class: HAZARDOUS WASTE | | | Required Container: STEEL / POLY | |
| EPA Waste Numbers D001 | | | | |
| Special Handling & Instructions: UHC: NONE | | | | |
| Remarks GHS02, GHS07, GHS08 | | | | |
| For Environmental Department Use Only - - - - Material Composition | | | | |
| Component | | Percent | Parts Per Million | |
| 1. LVP ALIPHATIC HYDROCARBON | | 40-50% | 400000-500000 ppm | |
| 2. PETROLEUM BASE OIL | | <35% | <350000 ppm | |
| 3. ALIPHATIC HYDROCARBON | | <25% | <250000 ppm | |
| 4. | | % | ppm | |
| 5. | | % | ppm | |
| Physical State: LIQUID | Waste Water: NO | Toxic: NO | Dioxin Listed: NO | |
| Corrosive: NO | pH: N/A | Reactive: NO | Flash Point: 138 F. | |
| High TOC: | Low TOC : | Land Ban: YES | Flammable: YES | |
| Reason for Classification: FLASH POINT <140 DEGREES F | | | | |
| Treatment Standards: 40 CFR 261 | | CAS# N/A | Generation Code: G11 | |
| Shipping Information | | | | |
| DOT Shipping Name: UN1268, WASTE PETROLEUM DISTILLATE, NOS, COMBUSTIBLE LIQUID, 3, PGIII, D001 | | | | |
| HAZ Class: 3 | Reportable Quantity: 100 LBS. | | Emergency Response Guide #: 128 | |
| EPA Waste Numbers: D001 | | | | |
| Certification: I certify that the above named materials are the only compounds included in the waste stream described and no other substance is present. | | <div>Prepared by</div> <div>Signed and Dated Copy On File</div> <div>Subase Env. Rep</div> <div>Review/Signature</div> | | |