262 Subase Kings Bay, Georgia		Waste Information Document (WID)				
As of 11/28/2023			WID Number 1993 - 262			
Waste Description: TITRATION FLUID FOR ACID # DETERMINATION/SPENT						
Waste Material label required?: YES				Hazardous Waste label required?: YES		
Waste Generation Process: TITRATION SOLVENT CONSISTS OF 500 ML TOLUENE, 5 ML WATER, AND 495 ML ISOPROPANOL, 20 GRAMS OF OIL TO BE TESTED ARE ADDED TO 100 ML TITRATION SOLVENT ALONG WITH 0.5 ML PARANAPTHOLBENZENE AND 0.1 ML KOH.						
Waste Class: HAZARDOUS WASTE			Required Container: STEEL / POLY			
EPA Waste Numbers D001,F005						
Special Handling & Instructions: UHC: NONE						
Remarks GHS02, GHS08						
For Environmental Department Use Only Material Composition						
Component			Percent		Parts Per Million	
1. TOLUENE				46%		460000ppm
2. ISOPROPANOL				46%		460000ppm
3. OIL				5%		50000ppm
4. P-NAPHTHOLBENZENE				1%		10000ppm
5. POTASSIUM HYDROXIDE				1%		10000ppm
Physical State: LIQUID	Waste Water: NO		То	Toxic: YES		Dioxin Listed: NO
Corrosive: NO	pH: 5.00			Reactive: NO		Flash Point: 100 F.
High TOC:	Low TOC :			Land Ban: YES		Flammable: YES
Reason for Classification: FLASH POINT BELOW 100 DEGREES F, CONTAINS 46% SPENT TOLUENE.						
Treatment Standards: 40 CFR 261 C			S# MIXTURE Genera		Genera	ation Code: G22
Shipping Information						
DOT Shipping Name: UN1993, WASTE FLAMMABLE LIQUID NOS (TOLUENE) 3, PGIII, D001, F005						
HAZ Class: 3 Reportable Qua		ortable Quantit	ntity: 100 LBS.		Emergency Response Guide #: 128	
EPA Waste Numbers: D001,F005						
Certification: I certify that the above named materials are the only compounds included in the waste stream described and no other substance is present. Prepared by Subase Env. Rep   Prepared by Signed and Dated Copy On File Review/Signature					-	