

856	Subase Kings Bay, Georgia		Waste Information Document (WID)	
As of 3/12/2018			WID Number 1993 - 856	
Waste Description: ISOCTANE AND OIL				
Waste Material label required?: YES			Hazardous Waste label required?: YES	
Waste Generation Process: OIL IS DISSOLVED IN ISOCTANE FOR PCB ANALYSIS. IF PCB COMPOUNDS ARE DETECTED, WASTE IS NOT PUT INTO THESE CONTAINERS.				
Waste Class: HAZARDOUS WASTE			Required Container: STEEL / POLY	
EPA Waste Numbers D001				
Special Handling & Instructions:				
Remarks GHS02				
For Environmental Department Use Only - - - - Material Composition				
Component		Percent	Parts Per Million	
1. ISOCTANE		90%	900000 ppm	
2. OIL		10%	100000 ppm	
3.		%	ppm	
4.		%	ppm	
5.		%	ppm	
Physical State: LIQUID	Waste Water: NO	Toxic: NO	Dioxin Listed: NO	
Corrosive: NO	pH: N/A	Reactive: NO	Flash Point: 50 F.	
High TOC:	Low TOC :	Land Ban: YES	Flammable: YES	
Reason for Classification: FLASH POINT = 50° F				
Treatment Standards: 40 CFR 261		CAS# SOLUTION	Generation Code: G22	
Shipping Information				
DOT Shipping Name: UN1993, WASTE FLAMMABLE LIQUID NOS (ISOCTANE) 3, PGII, D001.				
HAZ Class: HAZARDOUS WASTE	Reportable Quantity: 100 LBS.		Emergency Response Guide #: 128	
EPA Waste Numbers: D001				
Certification: I certify that the above named materials are the only compounds included in the waste stream described and no other substance is present.		<div style="display: flex; justify-content: space-between;"> <div> Prepared by Signed and Dated Copy On File </div> <div> Subase Env. Rep Review/Signature </div> </div>		